



15-CE22D

**CE22D - B/W CCD Camera DUAL VOLTAGE 12VDC & 24VAC**

<b>Optical Technology Base:</b>	1/3" CCD B/W
<b>Image Size ( Horz x Vert in mm)</b>	4.82 x 3.64
<b>Picture Elements (Horz x Vert in mm):</b>	EIA/NTSC: 510H x 492V - CCIR/PAL: 500H x 582V
<b>Resolution:</b>	420 Lines
<b>Minimum Illumination:</b>	0.1 Lux
<b>Horizontal Sync. Frequency:</b>	EIA/NTSC: 15.734KHz - CCIR/PAL: 15.625KHz
<b>Vertical Frequencies :</b>	EIA/NTSC: 60Hz - CCIR/PAL: 50Hz
<b>Clock Frequency :</b>	EIA/NTSC: 19.0699MHz - CCIR/PAL: 18.9375MHz
<b>Scanning:</b>	2:1 Interlace
<b>S/N Ratio:</b>	46 dB
<b>Electronic Shutter:</b>	1/10.000 / Sec Linear
<b>Auto Iris Lens:</b>	DC Drive/ AES / Video Drive
<b>Video Output :</b>	1V p-p, 75 ohms
<b>Audio Output :</b>	Max 2V p-p, 50 ohms
<b>Gamma :</b>	0.45
<b>White Balance :</b>	No
<b>Back Light Compensation:</b>	ON/OFF/Switchable
<b>Auto Gain:</b>	ON/OFF/Switchable
<b>Mirror Reverse Picture:</b>	NO
<b>Dimensions mm :</b>	103 x 52 x 56
<b>Weight :</b>	280g
<b>Power Supply :</b>	12VDC / 24VAC
<b>Power Consumption :</b>	170mA / 12VDC
<b>Storage Temperature:</b>	-30°C to +60°C

\* Pictures and specifications are subject to change without prior notice