



## CD56NV-IR Outdoor PTZ Nigh & Day Camera

<b>Image Sensor:</b>	1/4" CCD
<b>Active Pixels:</b>	752H x 582V
<b>Synchronization:</b>	Internal
<b>Video Output:</b>	VBS 1.0Vp-p /75 ohms
<b>White Balance:</b>	Auto/Manual
<b>Scanning Frequency:</b>	15625Khz (H) x 60Hz (V)
<b>Resolution:</b>	More than 480 Lines
<b>S/N Ratio:</b>	More than 50dB
<b>Electronic Shutter:</b>	1/3~1/10000s
<b>Lux:</b>	0.01 Lux
<b>Lens Focal Length:</b>	f=3.9~63mm 18x
<b>Iris/Zoom:</b>	Auto / Manual
<b>Tilt Speed:</b>	0~40°/s
<b>Pan Speed:</b>	0~80°/s
<b>Pan Rotation:</b>	360°
<b>Tilt Rotation:</b>	90° ( 180° Auto Overturn)
<b>Preset:</b>	128
<b>Patrol Function:</b>	6 Patrol Patterns
<b>Scanning Speed:</b>	0.5 ~ 30° /s
<b>Infrared Illuminator:</b>	High Brightness LEDx40pcs
<b>IR Wavelength:</b>	850 nm
<b>IR Project Distance:</b>	80 m

<b>IR Power Consumption:</b>	1.6 W
<b>Control of Infrared Lamp:</b>	Auto/Manual control on menu
<b>Service Life of Infrared Lamp:</b>	Over 20000 hours
<b>Alarm Four Channel Inputs:</b>	Normal Open, closing for alarm
<b>Alarm One Channel Output:</b>	Normal Open, Normal Close Output
<b>Power Supply:</b>	AC24V $\pm$ 10%
<b>Power Consumption:</b>	30VA
<b>Weight:</b>	10Kg
<b>Installation Style:</b>	Normal Open, closing for alarm
<b>Alarm One Channel Output:</b>	Plain Base Installation/Vehicle-Carried
<b>Relative Humidity:</b>	10-90%
<b>Operation Temperature:</b>	-35°C~55°C
<b>Waterproof Class:</b>	IP66

\* Pictures and specifications are subject to change without prior notice