



CZ65 - SONY CCD 520TVL 0 LUX 22X Optical Zoom A/F Day & Night RS485 Compatible w/ Pelco -D

Pick-up device:	1/4" SONY Super HAD High Resolution CCD
Picture elements HxV:	EIA/NTSC: 768H x 494V - CCIR/PAL: 752H x 582V
Horizontal resolution:	520 TVL
Vertical frequency :	EIA/NTSC: 59.94 HZ - CCIR/PAL: 50 HZ
Scanning system:	2:1 interlace
Optical Zoom:	22X Optical F=3.9mm~85.8mm, F1.6~3.7
Min Working Distance:	10mm (Wide end) ; 1000mm (Tele end)
S/N Ratio:	>50dB
Electronic shutter:	1/50s to 1/100.000sec
White Balance:	Auto; ATW; indoor / outdoor ; One push WB ; Manual
Auto Gain Control:	Auto (-3~28dB)
Automatic Exposure:	Auto/ Bright /Shutter/ IRIS
Back light Compensation:	5 Area
Privacy Zone:	8 Area
Focus Function:	Auto / Manual / Zoom in(out) trigger / Manual Trigger
Video Output:	BNC 1.0Vp-p 75 Ohms
Control Interface:	RS485 9600BPS compatible with Pelco Protocol
Working Voltage:	DC12V ± 10%
Consumption:	400mA

Weight:	650g - 1.43Lbs
Storage Temperature :	-30°C ~ 60°C
Operation Temperature :	-10°C ~ 50°C
	* Pictures and specifications are subject to change without prior notice